



Hankook Tires – Official tire partner



- *Every team that registers for the entire championship receives 1 free set of tires.*
- *Hankook Tires can and may only be purchased from Kronos Tires.*
- *Two official tire testdays are foreseen on March 21st 2019 and August 1st 2019, two weeks before the Eleven Sports 24 Hours of Zolder.*
- *Every type of tire is available on request.*

Your contact:

Charles-Antoine Hastir

+ 32 (0) 479 97 15 14

charly@kronostyres.com





Hankook Tires – Tehnical Data 2019

17-12-2018

SIZE	Type	RIM Width		Overall Diameter mm	Section Width mm	Tread Width mm	Circumference mm
		Recommend	Optium				
180/550R13	Soft	8.0-9.0	8,5	550	238	200	1727
240/570R13	Soft	10.0-11.0	10,5	574	290	250	1802
200/580R15	Medium	7.0-8.5	7,5	581	220	205	1824
260/610R16	Medium	9.0~10.5	10	607	276	260	1906
235/620R17	Medium	8.0-9.5	9	618	247	234	1941
240/640R18	Medium	8.0-9.5	9	645	245	225	2025
250/640R18	Medium	8.5-10.0	9,5	637	262	250	2000
260/660R18	Medium	9.0~10.5	10	661	282	254	2076
280/660R18	Medium	10.0~11.5	11	660	304	274	2072
280/680R18	Medium	10.0-11.5	11	680	306	285	2135
300/660R18	Medium	11.0~12.5	12	656	325	300	2060
300/680R18	Medium	11.0~12.5	12	675	331	300	2120
320/710R18	Medium	12.0~13.5	13	706	350	318	2217
Tire pressure target :			cold pressure front :	Cold pressure Rear:	Hot pressure: Front Axle / Rear Axle		
Front wheel drive:			1,5 - 1,6	1,7- 1,8	2.0-2,2 bar / 2,2-2,4 bar		
Rear wheel drive:			1,4 - 1,5	1,3 - 1,4	1.9-2,0 bar / 1,8-1.9 bar		
Camber :							
Front Axle:				max. 4° 00'			
Rear Axle:				max: 3° 30'			
WET tire : General 0,2 bar higher (cold pressure)							





Hankook Tires - Prices 2019

14-12-2018



Kronos Racing S.A. 37, rue des pieds d'Alouette 5100 Naninne Belgium	Charles-Antoine Hastir + 32 (0) 479 97 15 14 charly@kronostyres.com
---	---

Tyre Size	Compound available	Price without VAT
180/550R13	Slick & Wet	175
240/570R13	Slick & Wet	227
200/580R15	Slick & Wet	237
260/610R16	Slick & Wet	278
235/620R17	Slick & Wet	304
240/640R18	Slick & Wet	324
250/640R18	Slick & Wet	345
260/660R18	Slick & Wet	355
280/660R18	Slick & Wet	381
280/680R18	Slick & Wet	406
300/660R18	Slick & Wet	417
300/680R18	Slick & Wet	433
320/710R18	Slick & Wet	433

